




159 Crocker Park Blvd, 4th Floor
 Westlake, Ohio 44145
 Toll Free: 866-440-2123
 By Fax: 216-591-1276
 Email: info@standuppouches.net
 Web: www.standuppouches.net

Film Data Sheet

SS 115

Exterior



48 gauge Silver Metalized PET
 Black LLDPE

Interior

Physical Description:

Laminated 2.1 Mil Metalized PET with black sealant layer

Application:

This laminated material is silver in appearance with a black sealant layer. It has good moisture and oxygen barrier due to the metalized PET layer. The black sealant layer provides excellent UV and light protection. This film is ideal for toner cartridge, ink cartridge, and film packaging equipments.

Converting:

It can be converted in many ways: 2-seal pouch, 3-seal pouch, stand up, recloseable zipper, tear notch, and or tubing. It can also be surface printed (flexo-line or flexo-process).

Physical Properties:

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
Caliper	Micrometer	mils	2.1
Yield		sq.in./Lb	12,500
MVTR	Mocon	gms/100 sq.in./24 hrs	.02
OTR	ASTM-1434-66	cc/100 sq.in./24 hrs	.05
Burst	Mullen	psi	82
Tensile	ASTM D-882	lbs. at break	> 12 lbs/in
Tear MD	ASTM D-1004	lbs. at break	.95
Tear TD	ASTM D-1004	lbs. at break	.90
Puncture	FTMS 101C- 2065	lbs.	> 11
Optical Density			1.8-2.2 OD