

## Modular Access Control (MAC) Portal Specification Sheet

### MAC-4T

**General Features:**

Enclosure	20' Container
Approx. Shipping Weight*	7,200 lbs
Approx. Footprint (L X W)	20'-0" X 8'-0"
Approx. Shipping (L X W X H)*	20'-4" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	20'-4" X 9'-6" X 8'-6"

**Lifting Methods:**

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

**Office:**

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

**Turnstile Bay:**

Lanes	4
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

**Electrical Data:**

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	2.1
Demand Amps	9



Model No. M4TX

**Patents:**

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

