


PORTABLE AIR CONDITIONERS

Rent spot coolers! AIRPAC PORTABLE AIR CONDITIONERS <i>American Engineered. American Made. That's Cool!</i>	NEW	COOLIT® Series		PORTAPAC® Series			
	SpotHVAC	COOLIT2600	COOLIT3300	PAC36	PAC60	PAC96	PAC120
							
BTU/h Cool/Heat	14,000 - 11,000	13,500 - N/A	28,000 - N/A	36,000 - N/A	60,000 - N/A	96,000 - N/A	120,000 - N/A
Power Requirements <i>(Multiple choices for PAC's)</i>	115V	115V	208/230/1/60Hz	208/230/1/60Hz 208/230/3/60Hz 460/480/3/60Hz	208/230/1/60Hz 208/230/3/60Hz 460/480/3/60Hz	208/230/3/60Hz 460/480/3/60Hz	208/230/3/60Hz 460/480/3/60Hz
Amp Rating	10.8	11.7	16.0	41 @ 208/1 26 @ 208/3	59 @ 208/1 34 @ 208/3 18 @ 480/3	50 @ 208/3 26 @ 480/3	64 @ 208/3 32 @ 480/3
Fuse Size (amps)	15	15	20	60 @ 208/1 35 @ 208/3	80 @ 208/1 60 @ 208/3 25 @ 480/3	70 @ 208/3 35 @ 480/3	90 @ 208/3 45 @ 480/3
Supp Air Flow high/med/low	456/396/336	440	1,100	1,200	2,000	3,200	4,000
Return/Condenser CFM Max	N/A	680	2,050	2,200	3,100	4,500	6,200
Dimensions w x d x h (in.)	24 x 23-1/2 x 43	18-3/4 x 32-3/4 x 47-1/2	35-1/2 x 24 x 55	42 x 28-3/4 x 63-3/8	42 x 28-3/4 x 63-3/8	47-3/4 x 28-3/4 x 77	60-1/4 x 29-1/4 x 79-1/4
Weight (lbs.)	130	188	405	650	750	1,050	1,300
Control Features Control Panel/Thermostat	Electronic	Standard: Off - Fan - Cool Option 1: Electronic Thermostat with LCD Display Option 2: Electronic Programmable Thermostat with LCD Display Option 3: Electronic Programmable Thermostat with Internet Capability					
Cabinet Style	0.06" Aluminum	18 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.
Cabinet Finish	Diamond Tread	ABS Plastic	Powder Coated	Powder Coated	Powder Coated	Powder Coated	Powder Coated
NEMA Plug/Cord Length (ft.)	5-15P / 6	5-15P / 6	L6-20 / 5.5	Hard Wired	Hard Wired	Hard Wired	Hard Wired
Supp/Evap & Ret/Cond Air Size (in. dia.)	6 - 6	N/A - 10	N/A - 10	16 - 16	16 - 16	18 - 18	20 - 20
Supp/Evap Max. Ext. Static (IWG)	N/A	0.5	0.8	1.0	1.0	1.5	1.5
Supp/Evap & Ret/Cond Max Duct Length (ft.)	5 - 12	N/A - 25	N/A - 50	25 - 50	25 - 50	25 - 50	25 - 50
Condensate Management	Internal Pump	--2 Tanks, 2.5 gal. ea. & Internal Tank--					
Condensate Pump Lift (ft.)/Discharge ID (in.)	65 - 1/4	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8
Max. dB w/ Condenser Duct	N/A	52	58	N/A	N/A	N/A	N/A
Refrigerant Type/Charge per system (oz.)	R-410A / 21.1	R-410A / 18	R-410A / 48	R-410A / 80	R-410A / 88	R-410A / 88	R-410A / 88
Safety Certification	UL Listed	-ETL-Electrical Testing Laboratory-					

PORTABLE HEATERS

Rent clean, safe electric heat!	HEATIT™ Series				HEATPAC™ Series	
	HEATIT1.5	HEATIT3	HEATIT9	HEATPAC18	HEATPAC40	HEATPAC60
						
Heating Capacity						
kW	1.5	3	9	18	40	60
BTU/h	5,100	10,200	30,700	45,000 or 65,000	51,200/102,400/136,500	82,000 /164,000/205,000
Watts	1,500	3,000	9,000	13,000 or 19,000	16,000/32,000/40,000	24,000/48,000/60,000
Electrical Data						
Voltage	120/60/1	240/60/1	240/60/1	240/60/3	480/60/3	480/60/3
Power Consumption (amps)	12.5	12.5	37.5	31/47	20/40/50	30/60/75
Power Cord Gauge (AWG)	3 x 16	3 x 16	3 x 8	N/A	N/A	N/A
Cord Length (ft.)	9	9	9	----- Hard Wired -----		
Power Connection	NEMA 5-15P	NEMA 6-15P	NEMA 6-50 P	----- Hard Wired/CAM -----		
Airflow (CFM)	116	205	350	590	1765	1765
Dimensions						
w x d x h (in.)	8 x 12 x 12	10 x 14 x 15	12 x 23 x 18	14 x 30 x 18	20 x 46 x 25	20 x 46 x 25
Net Weight (lbs.)	15	17	48	52	125	125
Safety Certification	----- UL Listed -----					

SPECS AT A GLANCE

Cooling, Heating and Ventilating Equipment

AirPac E/S

(Office) 540-635-5011
(Direct) 540-635-5022
(Cell) 540-664-1774

AirPac Technology Park
888 Shenandoah Shores Rd.
Front Royal, VA 22630 USA

TEMPORARY HVAC

	GERO	JUH	COCH
Need temporary HVAC for Events or Facilities? We have it!			
Cool BTU/h 80/67, 95° F	4 tons	5 tons	12 tons
Heat BTU/h 60°, 50° F	42,000	57,500	N/A
Power Requirements	208/230/1/60Hz	208/230/3/60Hz	460/480/3/60Hz
Cool Amp Rating (amps)	23 ~ 20	35	30
Evaporator CFM Max	1236	2000	6000
Dimensions (w x d x h) (in.)	Indoor 23 x 17 x 71	48 x 55 x 35	34 x 74 x 74
Weight (lbs.)	Indoor 127	450	1,100
Control	On unit	T-stat	Manual or T-stat
Disconnect type	Plug	Plug	Internal Breaker
Cabinet Style	18 ga steel	18 ga. steel	16 ga. galv
Cabinet Finish	Powder Coated	Powder Coated	Powder Coated
Electrical Input Style	NEMA L6-30	Mini cam	HW or mini cam
Condensate Connection (in.)	Garden hose	Garden hose	Garden hose
Supply Air Size (in. dia.)	N/A	20	20
Return Air Size (in. dia.)	N/A	20	20

MOVING AIR

	FANIT2430
Rent air movers!	
Power Requirement	115V
Amp Rating (amps)	2.00/1.80
CFM High/Low	8575/ 6475
Dimension (w x d x h) (in.)	30 x 13-1/4 x 30-1/2
Weight (lbs.)	41
Description	360° Fan Rotation
Construction	Metal
Finish	Powder Coated
Power Cord Length (ft.)	18
Drive Type	Direct Drive
Fan Diameter (in.)	24
Mount Type	Portable Swivel Base
Decibal	65/57
Safety Certification	OSHA & UL Listed

The AirPac Advantage:

- Fast, friendly service
- Dependable, clean equipment

NEW FOR 2015

TentHVAC	HeroHVAC	SpotHVAC
		
----- 115 VAC, 11 amps -----		
----- EER: 10.1 -----		
----- Cooling Btu: 14,000 -----		
----- Heating Btu: 11,000 -----		
----- Dehumidify: 110 pints/day -----		
----- Air Flow: 3 speeds w/456 CFM max -----		
----- Thermostat Setting Range: 61° F to 89° F COOL / 61° F to 80° F HEAT -----		
----- 6" diameter x 8' Condenser Duct Extensions (x2) -----		
----- Internal Condensate Pump: >65' head -----		
----- Wheels: 12" back, 2" front swivel caster -----		
		24" x 24" Ceiling Tile
		2.5 Gallon Condensate Tank (CMS)
Dims: 20.2" W x 18" D x 35.2" H (+3" handle)	Dims: 24" W x 23.5" D x 39.5" H (+3" handle)	Dims: 24" W x 23.5" D x 39.5" H (+3" handle)
Weight: 95 lbs	Weight: 120 lbs	Weight: 130 Lbs
----- Optional Accessory: Nozzle @ 5" diameter x 18" (shown on all) -----		
----- Optional Accessory: Vinyl Cover (shown on TentHVAC) -----		

ACCESSORIES

- Air Duct – 20-inch diameter duct and straps
- Condensate pumps – 110V or 208V for high volume
- Power Distribution - Conductors (Cables), adapters
- Thermostats – 24V Wired or wireless
- Electric Heaters
- Flatbed Trailers
- Power Distribution Units (PDU)
- Diesel Generators

AirPac
Our Business is Cooling
and Heating Yours

TEMPORARY AIR CONDITIONING AND HEATING

888-324-7722
www.AirPacInc.com