



HYPRO®

The Ultimate Dicamba and 2,4-D Nozzle

ULTRA LO-DRIFT

The Ultra Lo-Drift's large air-filled droplets reduce spray drift, making it the ideal nozzle for Dicamba and 2,4-D applications.

Label Approved Nozzles from Hypro

Chemical	FastCap Part Number	Nozzle Only Part Number	Speed Range (15 GPA, 20" Spacing)
Engenia® Herbicide	FC-ULD120-04*	ULD120-04*	5.6-9.7 mph
	FC-ULD120-05*	ULD120-05*	7.0-12.1 mph
	FC-ULD120-06*	ULD120-06*	8.4-13.3 mph
Enlist Duo® herbicide with Colex-D® technology	FC-ULD120-04	ULD120-04	5.6-10.5 mph
	FC-ULD120-06	ULD120-06	8.4-13.3 mph
Enlist One™ Herbicide	FC-ULD120-04	ULD120-04	4.2-11.2 mph
	FC-ULD120-05	ULD120-05	4.8-13.1 mph
	FC-ULD120-06	ULD120-06	6.1-15.1 mph
FeXapan® plus VaporGrip® Technology	FC-ULD120-04	ULD120-04	5.6-7.9 mph
	FC-ULD120-05	ULD120-05	7.0-9.9 mph
XtendiMax® herbicide with VaporGrip® Technology	FC-ULD120-04	ULD120-04	5.6-7.9 mph
	FC-ULD120-05	ULD120-05	7.0-9.9 mph

*Must use a DRA on approved list see www.engeniatankmix.com for more information

Label Approved Nozzle Selection for Dicamba & 2, 4-D

ENGENIA® HERBICIDE

Approved Nozzles	Speed	15" Spacing					20" Spacing				
		Application Rate (gpa)									
		10	12.5	15	17.5	20	10	12.5	15	17.5	20
ULD120-04 *	Min Speed	11.2	9.0	7.5	6.4	5.6	8.4	6.7	5.6	4.8	4.2
FC-ULD120-04 *	Max Speed	15.0	15.0	12.9	11.1	9.7	14.5	11.6	9.7	8.3	7.3
ULD120-04 *	Min Speed	14.0	11.2	9.3	8.0	7.0	10.5	8.4	7.0	6.0	5.3
FC-ULD120-04 *	Max Speed	15.0	15.0	15.0	13.9	12.1	15.0	14.5	12.1	10.4	9.1
ULD120-06 *	Min Speed	-	13.4	11.2	9.6	8.4	12.6	10.1	8.4	7.2	6.3
FC-ULD120-06 *	Max Speed	-	15.0	15.0	15.0	13.3	15.0	15.0	13.3	11.4	10.0

*Must use a DRA on approved list see www.engeniatankmix.com for more information

ENLIST DUO® HERBICIDE WITH COLEX-D® TECHNOLOGY

Approved Nozzles	Speed	15" Spacing					20" Spacing				
		Application Rate (gpa)									
		10	12.5	15	17.5	20	10	12.5	15	17.5	20
ULD120-04	Min Speed	11.2	9.0	7.5	6.4	5.6	8.4	6.7	5.6	4.8	4.2
FC-ULD120-04	Max Speed	21.0	16.8	14.0	12.0	10.5	15.7	12.6	10.5	9.0	7.9
ULD120-06	Min Speed	16.8	13.4	11.2	9.6	8.4	12.6	10.1	8.4	7.2	6.3
FC-ULD120-06	Max Speed	26.6	21.3	17.7	15.2	13.3	19.9	15.9	13.3	11.4	10.0

ENLIST® ONE

Approved Nozzles	Speed	15" Spacing					20" Spacing				
		Application Rate (gpa)									
		10	12.5	15	17.5	20	10	12.5	15	17.5	20
ULD120-04	Min Speed	8.5	6.8	5.7	4.8	4.2	6.4	5.1	4.2	3.6	3.2
FC-ULD120-04	Max Speed	22.4	17.9	14.9	12.8	11.2	16.8	13.4	11.2	9.6	8.4
ULD120-04	Min Speed	9.7	7.8	6.5	5.5	4.8	7.3	5.8	4.8	4.2	3.6
FC-ULD120-04	Max Speed	26.2	21.0	17.5	15.0	13.1	19.6	15.7	13.1	11.2	9.8
ULD120-06	Min Speed	12.1	9.7	8.1	6.9	6.1	9.1	7.3	6.1	5.2	4.5
FC-ULD120-06	Max Speed	30.3	24.2	20.2	17.3	15.1	22.7	18.2	15.1	13.0	11.4

FEXAPAN® PLUS VAPORGRIP® TECHNOLOGY

Approved Nozzles	Speed	15" Spacing			20" Spacing		
		Application Rate (gpa)					
		15	17.5	20	15	17.5	20
ULD120-04	Min Speed	7.5	6.4	5.6	5.6	4.8	4.2
FC-ULD120-04	Max Speed	10.6	9.1	7.9	7.9	6.8	5.9
ULD120-05	Min Speed	9.3	8.0	7.0	7.0	6.0	5.3
FC-ULD120-05	Max Speed	13.2	11.3	9.9	9.9	8.5	7.4

XTENDIMAX® HERBICIDE WITH VAPORGRIP® TECHNOLOGY

Approved Nozzles	Speed	15" Spacing			20" Spacing		
		Application Rate (gpa)					
		15	17.5	20	15	17.5	20
ULD120-04	Min Speed	7.5	6.4	5.6	5.6	4.8	4.2
FC-ULD120-04	Max Speed	10.6	9.1	7.9	7.9	6.8	5.9
ULD120-05	Min Speed	9.3	8.0	7.0	7.0	6.0	5.3
FC-ULD120-05	Max Speed	13.2	11.3	9.9	9.9	8.5	7.4

Engenia is a registered trademark of BASF Corporation.

Enlist Duo and Colex-D are registered trademarks of Dow AgroSciences LLC. Enlist One is a trademark of Dow AgroSciences LLC.

Fexapan is a registered trademark of E. I. du Pont de Nemours and Company.

XtendiMax and VaporGrip are registered trademarks of Monsanto Technology LLC.



375 Fifth Avenue NW, New Brighton, MN 55112, USA 800-424-9776 hypro.pentair.com

Engenia is a registered trademark of BASF Corporation. Enlist Duo and Colex-D are registered trademarks of Dow AgroSciences LLC. Enlist One is a trademark of Dow AgroSciences LLC. Fexapan is a registered trademark of E. I. du Pont de Nemours and Company. XtendiMax and VaporGrip are registered trademarks of Monsanto Technology LLC. Pentair and Hypro are registered trademarks of Pentair. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

©2017 Pentair, Inc. All Rights Reserved.

Form 518 (3/18) Printed in USA